

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49				
Wet Bulb °F	50	50	50	50	50	55	55	55	55	55	60	60	60	60	60	65	65	65	65	65	65	70	70	70	70	70	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75		
Range °F	10	10	10	15	15	10	10	10	15	15	10	10	10	10	15	15	10	10	10	10	10	15	15	10	10	10	15	15	10	10	10	10	10	10	10	15	15	10	10	10	10	10	15	15	10	10	10	10	10	10	10	10	10
Approach °F	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12
Inlet Water Temperature °F	67	70	72	72	77	74	77	77	82	77	80	82	82	87	82	85	87	87	92	87	90	92	92	97	92	95	97	97	102	97	100	102	102	107	102	105	107	107	112	107	110	112	112	117	89.6	95	98.6	98.6					
Outlet Water Temperature °F	57	60	62	57	62	62	65	67	62	67	67	70	72	67	72	72	75	77	72	77	77	80	82	77	82	82	85	87	82	87	87	90	92	97	92	92	95	97	92	97	97	100	102	97	102	93.6	95	98.6	98.6				
Model Capacity (GPM)																																																					
SUN 19-611	385	514	600	313	482	422	561	650	348	523	466	616	707	385	572	526	687	797	435	641	590	767	888	488	718	665	862	992	550	804	753	963	1105	623	898	842	1082	1238	694	991	950	1219	NC	793	1114		862	722	967	856			
SUN 112-612L	611	818	956	496	766	671	893	1034	553	833	740	981	1126	611	909	838	1094	1270	691	1020	939	1223	1416	776	1145	1059	1375	1582	875	1281	1200	1536	1761	962	1431	1341	1725	1974	1106	1580	1514	1944	NC	1264	1776		1374	1150	1542	1365			